

MICRO-FRAISE D'ÉBAUCHE Z3 AVEC ARROSAGE PERIPHERIQUE  
 MIKROSCHRUPPFÄSER Z3 MIT PERIPHERER KÜHLUNG  
 ROUGHING MICRO ENDMILL Z3 WITH PERIPHERAL COOLING

**29510A-1-6**

Version du  
15.04.2024



ESHOP / EZI CUT

Compatibilité outil / matière  
 Werkzeug / Werkstoffverträglichkeit  
 Tool / Material compatibility

- 1/3
- 2/3
- 3/3

EZI - ALPHA 3  
 Groupe Vc [m/min]

ACIERS ALLIÉS ET NON ALLIÉS UNLEGIERTE STÄHLE NON-ALLOYED STEELS	Rm < 450 N/mm <sup>2</sup>	1a	240	●
	Rm 450 - 700 N/mm <sup>2</sup>	1b	140	●
	Rm 700 - 900 N/mm <sup>2</sup>	1c	120	●
	Rm < 1200 N/mm <sup>2</sup>	1d	70	●
ACIERS INOX ROSTFREIE STÄHLE STAINLESS STEELS	Rm < 650 N/mm <sup>2</sup>	2a	90	●
	Rm 650 - 950 N/mm <sup>2</sup>	2b	70	●
	Rm > 950 N/mm <sup>2</sup>	2c	50	●
ACIERS TREMPÉS GEHÄRTETE STÄHLE HARDENED STEELS	44 - 56 HRC	3a		
	57 - 67 HRC	3b		
MATERIAUX EXOTIQUES EXOTISCHE WERKSTOFFE EXOTIC MATERIALS	< 32 HRC	4a	40	●
	> 32 HRC	4b	30	●
GRAPHITE		5		
FONTES GUSS CAST IRON	< 32 HRC	6a	90	●
	> 32 HRC	6b	70	●
TITANE TITAN	Rm < 800 N/mm <sup>2</sup>	7a	60	●
	800 < Rm N/mm <sup>2</sup>	7b	40	●
ALLIAGES NICKEL NICKEL NICKEL ALLOYS	Rm < 1000 N/mm <sup>2</sup>	8a	40	●
	1000 < Rm N/mm <sup>2</sup>	8b	30	●
CUIVRE, LAITON, BRONZE KUPFER, MESSING, BRONZE COPPER, BRASS, BRONZE	Rm < 850 N/mm <sup>2</sup>	9a	340	●
	850 < Rm N/mm <sup>2</sup>	9b	240	●
ALUMINIUM	Si < 0.5%	10a		
	0.5% < Si < 5%	10b		
	Si > 5%	10c		
MATIERES SYNTHETIQUES KUNSTSTOFFE SYNTHETIC MATERIALS	Thermoplast	11a		
	Duraplast	11b		
MATIERES COMPOSITES FASERVERST. MATERIALEN COMPOSITE MATERIALS	Fibre de verre	12a		
	Fibre de carbone	12b		
METAUX PRECIEUX EDELMETALLE PRECIOUS MATERIALS	Or • Gold	13a	240	●
	Platine	13b	30	●



D (h10)	1
d (h6)	6
L	57
l1	2.5
l3	
d3	
R	
e	
Z	3
Chanfrein	0.15
K	
w° collision	10.9°