

FRAISE A FILETER  
 EWINDEFÄSER  
 THREADING CUTTER

**49380A-M2**

Version du  
 15.06.2020



Compatibilité outil / matière  
 Werkzeug / Werkstoffverträglichkeit  
 Tool / Material compatibility

- 1/3
- 2/3
- 3/3

EZI - ALPHA 3

Gruppe Vc [m/min]



ESHOP / EZI CUT

		Gruppe	Vc [m/min]	
ACIERS ALLIÉS ET NON ALLIÉS UNLEGIERTE STÄHLE NON-ALLOYED STEELS	Rm < 450 N/mm <sup>2</sup>	1a	260	●
	Rm 450 - 700 N/mm <sup>2</sup>	1b	150	●
	Rm 700 - 900 N/mm <sup>2</sup>	1c	125	●
	Rm < 1200 N/mm <sup>2</sup>	1d	80	●
ACIERS INOX ROSTFREIE STÄHLE STAINLESS STEELS	Rm < 650 N/mm <sup>2</sup>	2a	85	●
	Rm 650 - 950 N/mm <sup>2</sup>	2b	75	●
	Rm > 950 N/mm <sup>2</sup>	2c	60	●
ACIERS TREMPÉS GEHÄRTETE STÄHLE HARDENED STEELS	44 - 56 HRC	3a	45	●
	57 - 67 HRC	3b	25	●
MATÉRIAUX EXOTIQUES EXOTISCHE WERKSTOFFE EXOTIC MATERIALS	< 32 HRC	4a	50	●
	> 32 HRC	4b	30	●
GRAPHITE		5	180	●
FONTES GUSS CAST IRON	< 32 HRC	6a	80	●
	> 32 HRC	6b	65	●
TITANE TITAN	Rm < 800 N/mm <sup>2</sup>	7a	75	●
	800 < Rm N/mm <sup>2</sup>	7b	55	●
ALLIAGES NICKEL NICKEL NICKEL ALLOYS	Rm < 1000 N/mm <sup>2</sup>	8a	40	●
	1000 < Rm N/mm <sup>2</sup>	8b	30	●
CUIVRE, LAITON, BRONZE KUPFER, MESSING, BRONZE COPPER, BRASS, BRONZE	Rm < 850 N/mm <sup>2</sup>	9a	360	●
	850 < Rm N/mm <sup>2</sup>	9b	300	●
ALUMINIUM	Si < 0.5%	10a	400	●
	0.5% < Si < 5%	10b	320	●
	Si > 5%	10c	200	●
MATIÈRES SYNTHÉTIQUES KUNSTSTOFFE SYNTHETIC MATERIALS	Thermoplast	11a	170	●
	Duraplast	11b	120	●
MATIÈRES COMPOSITES FASERVERST. MATERIALIEN COMPOSITE MATERIALS	Fibre de verre	12a	160	●
	Fibre de carbone	12b	120	●
MÉTAUX PRÉCIEUX EDELMETALLE PRECIOUS MATERIALS	Or • Gold	13a	360	●
	Platine	13b	40	●



Ref	M2
Pas / Pitch	0.4
<b>O</b>	1.6
	48351(S)-1.60
	48380S-1.60
<b>D</b>	1.3
<b>d</b>	3
<b>L</b>	38
<b>l1</b>	3.2
<b>l3</b>	0.235
<b>d3</b>	
<b>R</b>	0.4
<b>e</b>	8.00
<b>Z</b>	3
<b>Chanfrein</b>	
<b>K</b>	0.264
<b>w° collision</b>	