

MICRO-FRAISE Z3 · MICRO-ENDMILL Z3 · MICRO-FRÄSER Z3



21048A-2.0 Version 10.09.2026



E25  
UF

ULTRAFINE GRADE HIGH-END GRADE WITH VERY HIGH HARDNESS AND TOUGHNESS FOR MICRO-MACHINING

$\lambda=30^{\circ}\text{-}35^{\circ}$   
 $\gamma=8^{\circ}$

VARIABLE HELIX ANGLES  $30^{\circ}$  -  $35^{\circ}$  AND CUTTING ANGLE  $8^{\circ}$

D/40  
45°

CHAMFER AT  $45^{\circ}$  / HEIGHT D/40

SIDE AND CENTER CUT

$l_1$   
1.5xD

CUTTING EDGE LENGTH 1.5xD

$l_3$   
8xD

CUTTING LENGTH 8xD

FITTING LENGTH LONG

IRREGULAR TOOTHINGS

$\lambda_2$   
 $\lambda_1$


VARIABLE HELIX ANGLES

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

| Product material compatibility |                          |                    |     |            |
|--------------------------------|--------------------------|--------------------|-----|------------|
| CATEGORY                       | MATERIAL                 | SPECIFICATION      | GRP | 21048A-2.0 |
| Alloyed and non-alloyed steels | Non-alloyed steels       | Rm < 450 N/mm²     | 1a  | ●●● 3/3    |
|                                |                          | Rm 450–700 N/mm²   | 1b  | ●●● 3/3    |
|                                |                          | Rm 700–900 N/mm²   | 1c  | ●●● 3/3    |
|                                |                          | Rm > 1200 N/mm²    | 1d  | ●●● 3/3    |
| Stainless steels               | Stainless steels         | Rm < 650 N/mm²     | 2a  | ●●● 3/3    |
|                                |                          | Rm 650–950 N/mm²   | 2b  | ●●● 3/3    |
|                                |                          | Rm > 950 N/mm²     | 2c  | ●●● 3/3    |
| Hardened steels                | Hardened steels          | 44–56 HRC          | 3a  | ●●○ 2/3    |
|                                |                          | 57–67 HRC          | 3b  | ●●○ 2/3    |
| Exotic materials               | Special alloys           | < 32 HRC           | 4a  | ●●○ 2/3    |
|                                |                          | > 32 HRC           | 4b  | ●●○ 2/3    |
| Graphite                       | Industrial graphite      |                    | 5   | ●●○ 2/3    |
| Cast iron                      | Grey / nodular cast iron | < 32 HRC           | 6a  | ●●● 3/3    |
|                                |                          | > 32 HRC           | 6b  | ●●● 3/3    |
| Titanium                       | Titanium alloys          | Rm < 600 N/mm²     | 7a  | ●●● 3/3    |
|                                |                          | 600 < Rm N/mm²     | 7b  | ●●● 3/3    |
| Nickel alloys                  | Inconel, Hastelloy       | Rm < 1000 N/mm²    | 8a  | ●●● 3/3    |
|                                |                          | Rm > 1000 N/mm²    | 8b  | ●●● 3/3    |
| Copper, brass, bronze          | Copper-based             | Rm < 850 N/mm²     | 9a  | ●○○ 1/3    |
|                                |                          | Rm > 850 N/mm²     | 9b  | ●○○ 1/3    |
| Aluminum                       | Aluminum alloys          | Si < 0.5%          | 10a | ●○○ 1/3    |
|                                |                          | 0.5% < Si < 5%     | 10b | ●○○ 1/3    |
|                                |                          | Si > 5%            | 10c | ●●○ 2/3    |
| Synthetic materials            | Engineering plastics     | Thermoplastic      | 11a | ○○○ 0/3    |
|                                |                          | Thermoset          | 11b | ○○○ 0/3    |
| Composite materials            | Reinforced composites    | Glass fiber / GFK  | 12a | ●○○ 1/3    |
|                                |                          | Carbon fiber / KFK | 12b | ●○○ 1/3    |
| Precious metals                | Gold, platinum, silver   | Gold               | 13a | ●●○ 2/3    |
|                                |                          | Platinum           | 13b | ●○○ 1/3    |

TECHNICAL DRAWING



DIMENSIONS

| NOMINAL DIMENSIONS |       |
|--------------------|-------|
| D (0 / -0.01)      | 2 mm  |
| d (h5)             | 3 mm  |
| L                  | 50 mm |
| l1                 | 3 mm  |
| l3                 | 16 mm |
| d3                 | –     |
| R                  | –     |
| e                  | –     |
| Z                  | 3     |
| Chamfer K          | 0.05  |
| w° collision angle | 1.7°  |



E-SHOP / EZI CUT



eskenazi.ch/eshop/21048A-2.0

All rights reserved