

FRAISE-PROFIL-ÉBAUCHE-MD-E2-+-EZI-ALPHA ·
ROUGHIN-ENDMILL-SC-E2-+-EZI-ALPHA · SCHAFT-
SCHRUPPFRÄSER-HM-E2-+-EZI-ALPHA



SWISS MADE

22510A-20 Version 12.09.2026

E2

SUBMICRON GRAIN GRADE
HIGH-SPEED MACHINING
OF ABRASIVE MATERIALS

$\lambda = 20^\circ$
 $\gamma = 6^\circ$

HELIX ANGLE 20° AND
CUTTING ANGLE 6°

45°

CHAMFER AT 45°

SIDE AND CENTER CUT

l_1
2.5xD

CUTTING EDGE LENGTH
2.5xD


FITTING LENGTH STANDARD

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

Product material compatibility				
CATEGORY	MATERIAL	SPECIFICATION	GRP	22510A-20
Alloyed and non-alloyed steels	Non-alloyed steels	Rm < 450 N/mm²	1a	●●○ 2/3
		Rm 450–700 N/mm²	1b	●●○ 2/3
		Rm 700–900 N/mm²	1c	●●○ 2/3
		Rm > 1200 N/mm²	1d	●○○ 1/3
Stainless steels	Stainless steels	Rm < 650 N/mm²	2a	●●○ 2/3
		Rm 650–950 N/mm²	2b	●●○ 2/3
		Rm > 950 N/mm²	2c	●●○ 2/3
Hardened steels	Hardened steels	44–56 HRC	3a	○○○ 0/3
		57–67 HRC	3b	○○○ 0/3
Exotic materials	Special alloys	< 32 HRC	4a	●○○ 1/3
		> 32 HRC	4b	●○○ 1/3
Graphite	Industrial graphite		5	○○○ 0/3
Cast iron	Grey / nodular cast iron	< 32 HRC	6a	●●● 3/3
		> 32 HRC	6b	●●● 3/3
Titanium	Titanium alloys	Rm < 600 N/mm²	7a	●●○ 2/3
		600 < Rm N/mm²	7b	●○○ 1/3
Nickel alloys	Inconel, Hastelloy	Rm < 1000 N/mm²	8a	●○○ 1/3
		Rm > 1000 N/mm²	8b	●○○ 1/3
Copper, brass, bronze	Copper-based	Rm < 850 N/mm²	9a	●●○ 2/3
		Rm > 850 N/mm²	9b	●●○ 2/3
Aluminum	Aluminum alloys	Si < 0.5%	10a	○○○ 0/3
		0.5% < Si < 5%	10b	○○○ 0/3
		Si > 5%	10c	○○○ 0/3
Synthetic materials	Engineering plastics	Thermoplastic	11a	○○○ 0/3
		Thermoset	11b	○○○ 0/3
Composite materials	Reinforced composites	Glass fiber / GFK	12a	○○○ 0/3
		Carbon fiber / KFK	12b	○○○ 0/3
Precious metals	Gold, platinum, silver	Gold	13a	●●○ 2/3
		Platinum	13b	●○○ 1/3

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS	
D (0 / -0.01)	20 mm
d (h5)	20 mm
L	104 mm
l1	38 mm
l3	–
d3	–
R	–
e	–
Z	4
Chamfer K	0.4
w° collision angle	–



E-SHOP / EZI CUT
eskenazi.ch/eshop/22510A-20