

FRAISE-UGV-MD-E2-+-EZI-DUR-POUR-MÉTAUX-DURS ·
ENDMILL-FOR-HSC-E2-+-EZI-DUR- · SCHAFTFRÄSER-
HSC-HM-E2-+-EZI-DUR-



SWISS MADE

23141X-14

Version 11.09.2026

E2

SUBMICRON GRAIN GRADE
HIGH-SPEED MACHINING
OF ABRASIVE MATERIALS

$\lambda = 45^\circ$
 $\gamma = -2^\circ$

HELIX ANGLE 45° AND
CUTTING ANGLE -2°

45°

CHAMFER AT 45°



SIDE AND EDGE CUT

l_1
3xD

CUTTING EDGE LENGTH
3xD



FITTING LENGTH LONG

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

Product material compatibility

CATEGORY	MATERIAL	SPECIFICATION	GRP	23141X-14
Alloyed and non-alloyed steels	Non-alloyed steels	Rm < 450 N/mm ²	1a	●○○ 1/3
		Rm 450–700 N/mm ²	1b	●○○ 1/3
		Rm 700–900 N/mm ²	1c	●○○ 1/3
		Rm > 1200 N/mm ²	1d	●●● 3/3
Stainless steels	Stainless steels	Rm < 650 N/mm ²	2a	●○○ 1/3
		Rm 650–950 N/mm ²	2b	●○○ 1/3
		Rm > 950 N/mm ²	2c	●○○ 1/3
Hardened steels	Hardened steels	44–56 HRC	3a	●●● 3/3
		57–67 HRC	3b	●●● 3/3
		< 32 HRC	4a	●●● 3/3
Exotic materials	Special alloys	> 32 HRC	4b	●●● 3/3
			5	●○○ 1/3
Graphite	Industrial graphite			
Cast iron	Grey / nodular cast iron	< 32 HRC	6a	●○○ 1/3
		> 32 HRC	6b	●○○ 1/3
Titanium	Titanium alloys	Rm < 600 N/mm ²	7a	●○○ 1/3
		600 < Rm N/mm ²	7b	●●○ 2/3
Nickel alloys	Inconel, Hastelloy	Rm < 1000 N/mm ²	8a	●●● 3/3
		Rm > 1000 N/mm ²	8b	●●● 3/3
Copper, brass, bronze	Copper-based	Rm < 850 N/mm ²	9a	○○○ 0/3
		Rm > 850 N/mm ²	9b	○○○ 0/3
Aluminum	Aluminum alloys	Si < 0.5%	10a	○○○ 0/3
		0.5% < Si < 5%	10b	○○○ 0/3
		Si > 5%	10c	○○○ 0/3
Synthetic materials	Engineering plastics	Thermoplastic	11a	○○○ 0/3
		Thermoset	11b	○○○ 0/3
Composite materials	Reinforced composites	Glass fiber / GFK	12a	○○○ 0/3
		Carbon fiber / KFK	12b	○○○ 0/3
Precious metals	Gold, platinum, silver	Gold	13a	○○○ 0/3
		Platinum	13b	○○○ 0/3

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS	
D (0 / -0.01)	14 mm
d (h5)	14 mm
L	110 mm
l1	32 mm
l3	–
d3	–
R	–
e	–
Z	6
Chamfer K	0.14
w° collision angle	–



E-SHOP / EZI CUT
eskenazi.ch/eshop/23141X-14

© 2026 Eskenazi SA — Carouge, Genève
All rights reserved