

SCIE-CIRCULAIRE-DENTURE-FINE-MD-H1S-+-EZI-ALPHA ·
SLITTING-SAW-FINE-PITCH-SC-H1S-+-EZI-ALPHA ·
KREISSÄGE-FEINVERZAHNT-HM-H1S-+-EZI-ALPHA



SWISS MADE

25500A-25-0.3 Version 12.09.2026

H1S

UNIVERSAL GRADE WITH GOOD WEAR RESISTANCE

$\lambda = 0^\circ$
 $\gamma = 6^\circ$

HELIX ANGLE 0° AND CUTTING ANGLE 6°

MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

Product material compatibility

CATEGORY	MATERIAL	SPECIFICATION	GRP	25500A-25-0.3
Alloyed and non-alloyed steels Non-alloyed steels		Rm < 450 N/mm ²	1a	●●● 3/3
		Rm 450–700 N/mm ²	1b	●●● 3/3
		Rm 700–900 N/mm ²	1c	●●● 3/3
		Rm > 1200 N/mm ²	1d	●●● 3/3
Stainless steels Stainless steels		Rm < 650 N/mm ²	2a	●●● 3/3
		Rm 650–950 N/mm ²	2b	●●● 3/3
		Rm > 950 N/mm ²	2c	●●● 3/3
Hardened steels Hardened steels		44–56 HRC	3a	○○○ 0/3
		57–67 HRC	3b	○○○ 0/3
Exotic materials Special alloys		< 32 HRC	4a	●○○ 1/3
		> 32 HRC	4b	●○○ 1/3
Graphite Industrial graphite			5	●●○ 2/3
Cast iron Grey / nodular cast iron		< 32 HRC	6a	●●○ 2/3
		> 32 HRC	6b	●●○ 2/3
Titanium Titanium alloys		Rm < 600 N/mm ²	7a	●●● 3/3
		600 < Rm N/mm ²	7b	●●● 3/3
Nickel alloys Inconel, Hastelloy		Rm < 1000 N/mm ²	8a	●●○ 2/3
		Rm > 1000 N/mm ²	8b	●●○ 2/3
Copper, brass, bronze Copper-based		Rm < 850 N/mm ²	9a	●○○ 1/3
		Rm > 850 N/mm ²	9b	●○○ 1/3
Aluminum Aluminum alloys		Si < 0.5%	10a	●○○ 1/3
		0.5% < Si < 5%	10b	●○○ 1/3
		Si > 5%	10c	●●○ 2/3
Synthetic materials Engineering plastics		Thermoplastic	11a	●○○ 1/3
		Thermoset	11b	●○○ 1/3
Composite materials Reinforced composites		Glass fiber / GFK	12a	●●○ 2/3
		Carbon fiber / KFK	12b	●●○ 2/3
Precious metals Gold, platinum, silver		Gold	13a	●●○ 2/3
		Platinum	13b	●○○ 1/3

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS

D (0 / -0.01)	25 mm
d (h5)	8 mm
L	–
l1	–
l3	–
d3	–
R	–
e	0.3 mm
Z	80
Chamfer K	–
w° collision angle	–



E-SHOP / EZI CUT
eskenazi.ch/eshop/25500A-25-0.3

© 2026 Eskenazi SA — Carouge, Genève
All rights reserved