

SCIE-CIRCULAIRE-DENTURE-FINE-MD-H1S-+-EZI-ALPHA ·  
SLITTING-SAW-FINE-PITCH-SC-H1S-+-EZI-ALPHA ·  
KREISSÄGE-FEINVERZAHNT-HM-H1S-+-EZI-ALPHA



SWISS MADE

25500A-25-1.6

Version 12.09.2026

H1S

UNIVERSAL GRADE WITH GOOD WEAR RESISTANCE

$\lambda = 0^\circ$   
 $\gamma = 6^\circ$

HELIX ANGLE 0° AND CUTTING ANGLE 6°


MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

Product material compatibility

| CATEGORY                       | MATERIAL                 | SPECIFICATION                | GRP | 25500A-25-1.6 |
|--------------------------------|--------------------------|------------------------------|-----|---------------|
| Alloyed and non-alloyed steels | Non-alloyed steels       | Rm < 450 N/mm <sup>2</sup>   | 1a  | ●●● 3/3       |
|                                |                          | Rm 450–700 N/mm <sup>2</sup> | 1b  | ●●● 3/3       |
|                                |                          | Rm 700–900 N/mm <sup>2</sup> | 1c  | ●●● 3/3       |
|                                |                          | Rm > 1200 N/mm <sup>2</sup>  | 1d  | ●●● 3/3       |
| Stainless steels               | Stainless steels         | Rm < 650 N/mm <sup>2</sup>   | 2a  | ●●● 3/3       |
|                                |                          | Rm 650–950 N/mm <sup>2</sup> | 2b  | ●●● 3/3       |
|                                |                          | Rm > 950 N/mm <sup>2</sup>   | 2c  | ●●● 3/3       |
| Hardened steels                | Hardened steels          | 44–56 HRC                    | 3a  | ○○○ 0/3       |
|                                |                          | 57–67 HRC                    | 3b  | ○○○ 0/3       |
| Exotic materials               | Special alloys           | < 32 HRC                     | 4a  | ●○○ 1/3       |
|                                |                          | > 32 HRC                     | 4b  | ●○○ 1/3       |
| Graphite                       | Industrial graphite      |                              | 5   | ●●○ 2/3       |
| Cast iron                      | Grey / nodular cast iron | < 32 HRC                     | 6a  | ●●○ 2/3       |
|                                |                          | > 32 HRC                     | 6b  | ●●○ 2/3       |
| Titanium                       | Titanium alloys          | Rm < 600 N/mm <sup>2</sup>   | 7a  | ●●● 3/3       |
|                                |                          | 600 < Rm N/mm <sup>2</sup>   | 7b  | ●●● 3/3       |
| Nickel alloys                  | Inconel, Hastelloy       | Rm < 1000 N/mm <sup>2</sup>  | 8a  | ●●○ 2/3       |
|                                |                          | Rm > 1000 N/mm <sup>2</sup>  | 8b  | ●●○ 2/3       |
| Copper, brass, bronze          | Copper-based             | Rm < 850 N/mm <sup>2</sup>   | 9a  | ●○○ 1/3       |
|                                |                          | Rm > 850 N/mm <sup>2</sup>   | 9b  | ●○○ 1/3       |
| Aluminum                       | Aluminum alloys          | Si < 0.5%                    | 10a | ●○○ 1/3       |
|                                |                          | 0.5% < Si < 5%               | 10b | ●○○ 1/3       |
|                                |                          | Si > 5%                      | 10c | ●●○ 2/3       |
| Synthetic materials            | Engineering plastics     | Thermoplastic                | 11a | ●○○ 1/3       |
|                                |                          | Thermoset                    | 11b | ●○○ 1/3       |
| Composite materials            | Reinforced composites    | Glass fiber / GFK            | 12a | ●●○ 2/3       |
|                                |                          | Carbon fiber / KFK           | 12b | ●●○ 2/3       |
| Precious metals                | Gold, platinum, silver   | Gold                         | 13a | ●●○ 2/3       |
|                                |                          | Platinum                     | 13b | ●○○ 1/3       |

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS

|                    |        |
|--------------------|--------|
| D (0 / -0.01)      | 25 mm  |
| d (h5)             | 8 mm   |
| L                  | –      |
| l1                 | –      |
| l3                 | –      |
| d3                 | –      |
| R                  | –      |
| e                  | 1.6 mm |
| Z                  | 40     |
| Chamfer K          | –      |
| w° collision angle | –      |



E-SHOP / EZI CUT  
eskenazi.ch/eshop/25500A-25-1.6

© 2026 Eskenazi SA — Carouge, Genève  
All rights reserved