

MICRO-FRAISE-D'ÉBAUCHE-AVEC-ARROSAGE-CENTRAL
· ROUGHING-MICRO-ENDMILL-WITH-INTERNAL-
COOLING · MIKROSCHRUPPFÄRER-MIT-
INNENKÜHLUNG



SWISS MADE

28525A-1.5

Version 10.09.2026

E2
SUBMICRON GRAIN GRADE
HIGH-SPEED
MACHINING OF
ABRASIVE
MATERIALS

$\lambda=45^{\circ}-47^{\circ}$
 $\gamma=15^{\circ}$
VARIABLE HELIX
ANGLES 45° -
47° AND
CUTTING ANGLE
15°

45°
CHAMFER AT 45°

SIDE AND
CENTER CUT

l_1
1.5xD
CUTTING EDGE
LENGTH 1.5XD

l_3
3xD
CUTTING
LENGTH 3XD

FITTING LENGTH
STANDARD

IRREGULAR
TOOTHING

λ_2
 λ_1
VARIABLE HELIX
ANGLES


MATERIAL COMPATIBILITY

●●● Excellent (3/3) ●●○ Good (2/3) ●○○ Possible (1/3) ○○○ Not recommended

Product material compatibility

CATEGORY	MATERIAL	SPECIFICATION	GRP	28525A-1.5
Alloyed and non-alloyed steels	Non-alloyed steels	Rm < 450 N/mm²	1a	●●● 3/3
		Rm 450–700 N/mm²	1b	●●● 3/3
		Rm 700–900 N/mm²	1c	●●● 3/3
		Rm > 1200 N/mm²	1d	●●○ 2/3
Stainless steels	Stainless steels	Rm < 650 N/mm²	2a	●●● 3/3
		Rm 650–950 N/mm²	2b	●●● 3/3
		Rm > 950 N/mm²	2c	●●● 3/3
Hardened steels	Hardened steels	44–56 HRC	3a	○○○ 0/3
		57–67 HRC	3b	○○○ 0/3
Exotic materials	Special alloys	< 32 HRC	4a	●●○ 2/3
		> 32 HRC	4b	●●○ 2/3
Graphite	Industrial graphite		5	●○○ 1/3
Cast iron	Grey / nodular cast iron	< 32 HRC	6a	●●● 3/3
		> 32 HRC	6b	●●● 3/3
Titanium	Titanium alloys	Rm < 600 N/mm²	7a	●●● 3/3
		600 < Rm N/mm²	7b	●●● 3/3
Nickel alloys	Inconel, Hastelloy	Rm < 1000 N/mm²	8a	●●○ 2/3
		Rm > 1000 N/mm²	8b	●●○ 2/3
Copper, brass, bronze	Copper-based	Rm < 850 N/mm²	9a	●●● 3/3
		Rm > 850 N/mm²	9b	●●● 3/3
Aluminum	Aluminum alloys	Si < 0.5%	10a	○○○ 0/3
		0.5% < Si < 5%	10b	○○○ 0/3
		Si > 5%	10c	○○○ 0/3
Synthetic materials	Engineering plastics	Thermoplastic	11a	○○○ 0/3
		Thermoset	11b	○○○ 0/3
Composite materials	Reinforced composites	Glass fiber / GFK	12a	●○○ 1/3
		Carbon fiber / KFK	12b	●○○ 1/3
Precious metals	Gold, platinum, silver	Gold	13a	●●● 3/3
		Platinum	13b	●●○ 2/3

TECHNICAL DRAWING



DIMENSIONS

NOMINAL DIMENSIONS	
D (0 / -0.01)	1.5 mm
d (h5)	3 mm
L	38 mm
l1	2.5 mm
l3	4.5 mm
d3	–
R	–
e	–
Z	3
Chamfer K	0.15
w° collision angle	5.8°



ESUCH/ETZCUT

© 2026 ezi AG. Alle Rechte vorbehalten.



E-SHOP / EZICUI
eskenazi.ch/eshop/28525A-1.5

© 2026 Eskenazi SA — Carouge, Genève
All rights reserved