


MICRO-FORET-Z:2-AVEC-ARROSAGE-CENTRAL-MD-E25-UF-+-EZI-SMOOTH-D:2.50-D:3-L:63-L2:30-L3:32.5 · MICRO-FLUTES-DRILL-Z:2-WITH-THROUGH-COOLANT-CARBIDE-E25-UF-+-COATING-EZI-SMOOTH-D:2.50-D:3-L:63-L2:30-L3:32.5 · MIKRO-BOHRER-Z:2-MIT-INNENKÜHLUNG-HM-E25-UF-+-BESCHICHTUNG-EZI-SMOOTH-D:2.50-D:3-L:63-L2:30-L3:32.5



48480S-2.50 Version du 11.09.2026



NUANCE SUBMICROGRAINS
USINAGE HAUTE VITESSE DE
MATIÈRES ABRASIVES



ANGLE D'HÉLICE 30°



ANGLE DE POINTE 135°



LONGUEUR UTILE LONGUE



ARROSAGE CENTRAL

COMPATIBILITÉ MATIÈRE

●●● Excellent (3/3) ●●○ Bon (2/3) ●○○ Possible (1/3) ○○○ Non recommandé

Compatibilité du produit avec les matières				
CATÉGORIE	MATIÈRE	SPÉCIFICATION	GRP	48480S-2.50
Aciers alliés et non alliés	Aciers non alliés	Rm < 450 N/mm²	1a	●●● 3/3
		Rm 450–700 N/mm²	1b	●●● 3/3
		Rm 700–900 N/mm²	1c	●●● 3/3
		Rm > 1200 N/mm²	1d	●●● 3/3
Aciers Inox	Aciers inoxydables	Rm < 650 N/mm²	2a	●●● 3/3
		Rm 650–950 N/mm²	2b	●●● 3/3
		Rm > 950 N/mm²	2c	●●● 3/3
Aciers trempés	Aciers durcis	44–56 HRC	3a	●○○ 1/3
		57–67 HRC	3b	○○○ 0/3
Matériaux exotiques	Alliages spéciaux	< 32 HRC	4a	●●● 3/3
		> 32 HRC	4b	●●● 3/3
Graphite	Graphite industriel		5	●●● 3/3
Fontes	Fonte grise / nodulaire	< 32 HRC	6a	●●● 3/3
		> 32 HRC	6b	●●● 3/3
Titane	Alliages titane	Rm < 600 N/mm²	7a	●●● 3/3
		600 < Rm N/mm²	7b	●●● 3/3
Alliages Nickel	Inconel, Hastelloy	Rm < 1000 N/mm²	8a	●●○ 2/3
		Rm > 1000 N/mm²	8b	●●○ 2/3
Cuivre, laiton, bronze	Cuivreux	Rm < 850 N/mm²	9a	●●● 3/3
		Rm > 850 N/mm²	9b	●●● 3/3
Aluminium	Alliages aluminium	Si < 0.5%	10a	●●● 3/3
		0.5% < Si < 5%	10b	●●● 3/3
		Si > 5%	10c	●●● 3/3
Matières synthétiques	Plastiques techniques	Thermoplastique	11a	●●● 3/3
		Thermodurcissable	11b	●●● 3/3
Matières composites	Composites renforcés	Fibre de verre / GFK	12a	●●● 3/3
		Fibre de carbone / KFK	12b	●●● 3/3
Métaux précieux	Or, platine, argent	Or	13a	●●● 3/3
		Platine	13b	●●○ 2/3

DESSIN TECHNIQUE



DIMENSIONS

DIMENSIONS NOMINALES	
D (0 / -0.01)	2.5 mm
d (h5)	3 mm
L	57 mm
l1	21 mm
l3	32.5 mm
d3	–
R	–
e	–
Z	2
Chanfrein K	–
w° collision	0.4°



E-SHOP / EZI CUT
eskenazi.ch/eshop/48480S-2.50

© 2026 Eskenazi SA — Carouge, Genève
Tous droits réservés