

MICRO-FORET-Z:2-AVEC-ARROSAGE-CENTRAL-MD-E25-UF-+-EZI-SMOOTH-D:2.70-D:3-L:63-L2:33-L3:35.5 · MICRO-FLUTES-DRILL-Z:2-WITH-THROUGH-COOLANT-CARBIDE-E25-UF-+-COATING-EZI-SMOOTH-D:2.70-D:3-L:63-L2:33-L3:35.5 · MIKRO-BOHRER-Z:2-MIT-INNENKÜHLUNG-HM-E25-UF-+-BESCHICHTUNG-EZI-SMOOTH-D:2.70-D:3-L:63-L2:33-L3:35.5



48480S-2.70 Version du 11.09.2026


 NUANCE SUBMICROGRAINS USINAGE HAUTE VITESSE DE MATIÈRES ABRASIVES	 ANGLE D'HÉLICE 30°	 ANGLE DE POINTE 135°	 LONGUEUR UTILE LONGUE	 ARROSAGE CENTRAL
--	---	---	--	---

COMPATIBILITÉ MATIÈRE

●●● Excellent (3/3) ●●○ Bon (2/3) ●○○ Possible (1/3) ○○○ Non recommandé

Compatibilité du produit avec les matières				
CATÉGORIE	MATIÈRE	SPÉCIFICATION	GRP	48480S-2.70
	Aciers alliés et non alliés Aciers non alliés	Rm < 450 N/mm ²	1a	●●● 3/3
		Rm 450–700 N/mm ²	1b	●●● 3/3
		Rm 700–900 N/mm ²	1c	●●● 3/3
		Rm > 1200 N/mm ²	1d	●●● 3/3
	Aciers Inox Aciers inoxydables	Rm < 650 N/mm ²	2a	●●● 3/3
		Rm 650–950 N/mm ²	2b	●●● 3/3
		Rm > 950 N/mm ²	2c	●●● 3/3
	Aciers trempés Aciers durcis	44–56 HRC	3a	●○○ 1/3
		57–67 HRC	3b	○○○ 0/3
	Matériaux exotiques Alliages spéciaux	< 32 HRC	4a	●●● 3/3
		> 32 HRC	4b	●●● 3/3
	Graphite Graphite industriel		5	●●● 3/3
	Fontes Fonte grise / nodulaire	< 32 HRC	6a	●●● 3/3
		> 32 HRC	6b	●●● 3/3
	Titane Alliages titane	Rm < 600 N/mm ²	7a	●●● 3/3
		600 < Rm N/mm ²	7b	●●● 3/3
	Alliages Nickel Inconel, Hastelloy	Rm < 1000 N/mm ²	8a	●●○ 2/3
		Rm > 1000 N/mm ²	8b	●●○ 2/3
	Cuivre, laiton, bronze Cuivreux	Rm < 850 N/mm ²	9a	●●● 3/3
		Rm > 850 N/mm ²	9b	●●● 3/3
	Aluminium Alliages aluminium	Si < 0.5%	10a	●●● 3/3
		0.5% < Si < 5%	10b	●●● 3/3
		Si > 5%	10c	●●● 3/3
	Matières synthétiques Plastiques techniques	Thermoplastique	11a	●●● 3/3
		Thermodurcissable	11b	●●● 3/3
	Matières composites Composites renforcés	Fibre de verre / GFK	12a	●●● 3/3
		Fibre de carbone / KFK	12b	●●● 3/3
	Métaux précieux Or, platine, argent	Or	13a	●●● 3/3
		Platine	13b	●●○ 2/3

DESSIN TECHNIQUE



DIMENSIONS

DIMENSIONS NOMINALES	
D (0 / -0.01)	2.7 mm
d (h5)	3 mm
L	57 mm
l1	21 mm
l3	35.5 mm
d3	–
R	–
e	–
Z	2
Chanfrein K	–
w° collision	0.2°



E-SHOP / EZI CUT
eskenazi.ch/eshop/48480S-2.70

© 2026 Eskenazi SA — Carouge, Genève
Tous droits réservés